

Telehandler / Zoom Boom

Used Telehandler Kansas - Telehandlers are commonly known by a variety of names such as Cherry pickers, telescopic handlers, boom lifts and teleporters. This industrial machine is commonly used in a variety of industries and in agriculture. Similar to a crane and a forklift as it has a boom allowing it to extend forwards and upwards. Many different attachments can be used at the end of the articulating boom to facilitate a wide number of jobs. Common attachments include pallet forks, a winch, a bucket or a muck grab. The main telehandler attachment is the pallet forks. They allow the operator to transport loads to and from locations that are considered unreachable with a regular forklift. Telehandlers allow cargo pallets to be transported from trailers and placed on racking, rooftops or other difficult to reach locations. Typically, high locations would traditionally require a crane; however, telehandlers can facilitate these tasks easily and efficiently. It can be expensive and impractical to rely on a crane or expansive industrial equipment to finish particular tasks. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Moving items from unreachable locations that cannot be completed with a backhoe loader or wheeled loader give telehandlers a huge advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. Interestingly enough, the machines' main advantage is also its' biggest limitation. When raising or extending with heavy loads, the boom functions similar to a lever. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A machine with a 5K lb. capacity could safely lift 400 lbs. while fully extended using a retracted low boom angle. Raising the same piece of equipment 70 degrees could allow this machine with a five thousand pound lift capability and retracted boom to support up to ten thousand pounds. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. There are sensors and computers available on newer models. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. Compact telehandler models are available in a variety of different weights, reach, sizes and boom designs. If the machine weighs in at eleven thousand pounds or less, it can be part of the compact category. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. Compact models rely on a low pivot boom to facilitate better cab visibility as the operator transports loads. There are narrower and smaller dimensions offered with the compact telehandler. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. The versatility of the compact telehandler makes it popular in a variety of applications. Telehandlers can function as a pick and place unit or a tool carrier. Compact units are ideal for cramped locations. Residential services are often employed during framing and for jobs with height restrictions. These machines can facilitate internal building access. Compact units are popular in multi-story construction, nurseries, strip malls, landscaping, masonry, garage facilities and erecting steel among other applications. Agri-business and farming applications rely on telehandlers for a variety of jobs. Telehandlers are made with two or four-wheel drive as well as crab steering. The unit can travel over longer ranges at higher speeds with two-wheel drive,

making it ideal for moving throughout job sites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. Compact telehandlers have numerous cab environments to choose from. There is a rollover protective cage to enhance safety on less expensive models. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Operators enjoy spacious accommodation for ultimate comfort. Additional features such as cup holders, air conditioning, tilt steering, suspension seats and satellite radio are all options. The numerous attachment options are facilitated with high-pressure and high-flow auxiliary hydraulics. These attachments increase the functions the machine is capable of. Ground engaging work is often completed by compact units. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. Light-duty to heavy-duty buckets can be attached for transferring material, side-shifting and rotating fork carriages are relied on for pick and place situations, augers for drilling post holes or planting trees or pier supports, truss booms for extending reach, crane hooks, brooms for sweeping and more. Skid steer options are made for compact telehandler designs and ultimate versatility.